

Trunnion Ball Valve Top Entry

Special valve constructions to allow easy on-site maintenance and disassembly with quick access to ball and seats for inspection and repair.



GENERAL CONSTRUCTION

ERREESSE Top Entry valves are suitable for compression and re-injection systems, transmission pipelines, metering skids, Pig-launchers and receiving stations, Off-Shore and On-Shore platforms, gas storage and separations systems suitable for a wide range of high risk industry applications from severe abrasive and slurry to high temperature and cryogenic services, from subsea and LNG plants to topside installations.

ERREESSE Top Entry valves can be welded directly onto the pipeline or to the manifold.

MATERIALS OF CONSTRUCTIONS

Low Temperature and Low Alloy Carbon Steel
Stainless steel, Duplex and Super Duplex
Nickel alloys
Titanium
Bronze

APPLICATIONS

UTILITY

CORROSIVE & DIRTY

LOW TEMPERATURE

HIGH PRESSURE

STANDARD FEATURES

Construction	One piece bolted bonnet
Port	Reduced bore, full bore or fully piggable
Stem retention	Anti blow-out stem
Leakage rate	ISO 5208 rate A soft seated, rate B,C, D metal seated
Antistatic device	Included, the ball valve design includes an electric conductive connection between the internal parts of the ball valve and the body, providing the anti-static function.
Pressure relief	Automatic cavity relief to prevent overpressure in body cavity (self-relieving seats)
Sealing	Bi-directional, Double block & bleed (DBB) with sealing in both directions (DIB-1&2 upon request) Metal seated with Tungsten or Chrome Carbide coatings Primary metal secondary soft (PMSS) with differential hardness between the ball and seat to prevent galling of the substrate Soft seated with thermoplastic polymers (Nylon, Devlon, PEEK, PCTFE), special polymers upon request Elastomers FKM, HNBR, EPDM O-Rings, special elastomers upon request
Drain	Drilled and threaded connections for all sizes
Vent	Drilled and threaded vent connections for sizes ≥ DN150 (6") < DN150 upon request
Stem grease injectors	Included for all sizes
Seat grease injectors	Included for sizes ≥ DN150 (6"), < DN150 upon request
Lifting points	Included for sizes ≥ DN150 (6") or on valves of 250 kg min
Support feet	Included for sizes ≥ DN150 (6") or on valves of 250 kg min
Stem extension	Not foreseen for this model
Valve operation	Lever, Gear box or Actuator with position indicator and locking device
Material testing	Pressure containing & controlling parts to EN 10204 3.1 Materials in Sour Service according to NACE MR0175, MR0103, ISO 15156 Non-destructive testing (NDT) to API 6D, ASME B16.34
Valve testing	Hydrostatic & pneumatic testing to API 6D, ASME B16.34, ISO 5208 (other upon request)

TECHNICAL DATA

Design	API 6D, API 6DSS, API 6A, ASME B16.34, ISO 14313, ISO 10423, ISO 17292
Design pressure	ASME B16.34, EN 1092-1, ISO 17292
Body wall thickness	ASME B16.34, ASME VIII Div. I, ISO 17292
Face to Face	API 6D, ASME B16.10 Long pattern
Temperature range	-50° to 200°C (-58° to 392°F)
Pressures range	PN20 (ANSI 150) to PN420 (ANSI 2500)
Size range	DN15 (1/2") to DN1400 (56")
End connections	ASME B16.5 ≤ DN600 (24") Flanged RF,FF,RTJ MSS-SP-44 = DN550 (22") Flanged RF,FF,RTJ ASME B16.47 A ≥ DN650 (26") Flanged RF,FF,RTJ ASME B16.25 Butt-Weld BW Clump (HUB)

APPROVALS

Safety Integrity Level	SIL 3
Fire Safe	API 607, API 6FA, BS 6755, ISO 10497-5
Area Classification	ATEX 94/9/EC
Pressure Equipment Directive	PED 97/23/EC
Fugitive Emission	ISO 15848/1
Construction	API 6D, API 6DSS

All data stated in this sheet are subject to changes and amendments which will be not notified and are for general information only.

Erreesse disclaims any liability for damages occurred due to his wrong use and interpretation.

Erreesse s.r.l. Via delle Betulle 8A/8B/8C, 28075 Grignasco (NO) Italy - 0039 0163 415901 - 0039 0163 415941 - sales@erreesse-valves.com